



MALAYSIAN STANDARD

MS CISPR 16-1-4:2012

**Specification for radio disturbance and immunity measuring apparatus and methods
- Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements
(Second revision)
(CISPR 16-1-4:2010, IDT)**

ICS: 33.100.10; 33.100.20

Descriptors: specification, radio disturbance, immunity, measuring apparatus, method, ancillary equipment, radiated disturbance

© Copyright 2012

DEPARTMENT OF STANDARDS MALAYSIA

DEVELOPMENT OF MALAYSIAN STANDARDS

The **Department of Standards Malaysia (STANDARDS MALAYSIA)** is the national standards and accreditation body of Malaysia.

The main function of STANDARDS MALAYSIA is to foster and promote standards, standardisation and accreditation as a means of advancing the national economy, promoting industrial efficiency and development, benefiting the health and safety of the public, protecting the consumers, facilitating domestic and international trade and furthering international cooperation in relation to standards and standardisation.

Malaysian Standards (MS) are developed through consensus by committees which comprise balanced representation of producers, users, consumers and others with relevant interests, as may be appropriate to the subject at hand. To the greatest extent possible, Malaysian Standards are aligned to or are adoption of international standards. Approval of a standard as a Malaysian Standard is governed by the Standards of Malaysia Act 1996 [Act 549]. Malaysian Standards are reviewed periodically. The use of Malaysian Standards is voluntary except in so far as they are made mandatory by regulatory authorities by means of regulations, local by-laws or any other similar ways.

STANDARDS MALAYSIA has appointed **SIRIM Berhad** as the agent to develop, distribute and sell the Malaysian Standards.

For further information on Malaysian Standards, please contact:

Department of Standards Malaysia
Ministry of Science, Technology and Innovation
Level 1 & 2, Block 2300, Century Square
Jalan Usahawan
63000 Cyberjaya
Selangor Darul Ehsan
MALAYSIA

Tel: 60 3 8318 0002
Fax: 60 3 8319 3131
<http://www.standardsmalaysia.gov.my>

E-mail: central@standardsmalaysia.gov.my

OR **SIRIM Berhad**
(Company No. 367474 - V)
1, Persiaran Dato' Menteri
Section 2, P.O. Box 7035
40700 Shah Alam
Selangor Darul Ehsan
MALAYSIA

Tel: 60 3 5544 6000
Fax: 60 3 5510 8095
<http://www.sirim.my>

E-mail: msonline@sirim.my

CONTENTS

Committee representation.....v

National foreword.....vi

Foreword.....vii

1 Scope.....8

2 Normative references.....8

3 Terms, definitions and abbreviations9

 3.1 Terms and definitions9

 3.2 Abbreviations.....12

4 Antennas for measurement of radiated radio disturbance12

 4.1 General12

 4.2 Physical parameter for radiated emission measurements12

 4.3 Frequency range 9 kHz to 150 kHz13

 4.3.1 General13

 4.3.2 Magnetic antenna13

 4.3.3 Shielding of loop antenna.....13

 4.4 Frequency range 150 kHz to 30 MHz.....13

 4.4.1 Electric antenna13

 4.4.2 Magnetic antenna14

 4.4.3 Balance/cross-polar performance of antennas14

 4.5 Frequency range 30 MHz to 1 000 MHz.....14

 4.5.1 General14

 4.5.2 Low-uncertainty antenna for use if there is an alleged non-compliance to the *E*-field limit.....14

 4.5.3 Antenna characteristics.....14

 4.5.4 Balance of antenna16

 4.5.5 Cross-polar response of antenna18

 4.6 Frequency range 1 GHz to 18 GHz.....18

 4.7 Special antenna arrangements – Loop antenna system19

5 Test sites for measurement of radio disturbance field strength for the frequency range of 30 MHz to 1 000 MHz19

 5.1 General19

 5.2 OATS19

 5.2.1 General19

 5.2.2 Weather protection enclosure20

 5.2.3 Obstruction-free area20

 5.2.4 Ambient radio frequency environment of a test site.....21

 5.2.5 Ground plane.....22

 5.2.6 OATS validation procedure22

 5.3 Test site suitability for other ground-plane test sites26

 5.3.1 General26

 5.3.2 Normalized site attenuation for alternative test sites26

 5.3.3 Site attenuation.....30

 5.3.4 Conducting ground plane30

 5.4 Test site suitability without ground plane31

 5.4.1 Measurement considerations for free space test sites, as realized by fully-absorber-lined shielded enclosures.....31

 5.4.2 Site performance32

 5.4.3 Site validation criteria.....40

 5.5 Evaluation of set-up table and antenna tower40

5.5.1	General	40
5.5.2	Evaluation procedure for set-up table influences	40
6	Reverberating chamber for total radiated power measurement	42
6.1	General	42
6.2	Chamber	42
6.2.1	Chamber size and shape.....	42
6.2.2	Door, openings in walls, and mounting brackets	42
6.2.3	Stirrers	43
6.2.4	Test for the efficiency of the stirrers	43
6.2.5	Coupling attenuation	44
7	TEM cells for immunity to radiated disturbance measurement.....	45
8	Test sites for measurement of radio disturbance field strength for the frequency range 1 GHz to 18 GHz.....	45
8.1	General	45
8.2	Reference test site	45
8.3	Validation of the test site.....	45
8.3.1	General	45
8.3.2	Acceptance criterion for site validation	46
8.3.3	Site validation procedures – evaluation of S_{VSWR}	47
8.4	Alternative test sites	59
9	Common mode absorption devices.....	59
9.1	General	59
9.2	CMAD S -parameter measurements	59
9.3	CMAD test jig	59
9.4	Measurement method using the TRL calibration	61
9.5	Specification of ferrite clamp-type CMAD	63
9.6	CMAD performance (degradation) check using spectrum analyzer and tracking generator	63
Annex A (normative)	Parameters of antennas.....	66
Annex B (normative)	Monopole (1 m rod) antenna performance equations and characterization of the associated antenna matching network	73
Annex C (normative)	Loop antenna system for magnetic field induced-current measurements in the frequency range of 9 kHz to 30 MHz.....	78
Annex D (normative)	Construction details for open area test sites in the frequency range of 30 MHz to 1 000 MHz (see Clause 5).....	87
Annex E (normative)	Validation procedure of the open area test site for the frequency range of 30 MHz to 1 000 MHz (see Clause 5).....	91
Annex F (informative)	Basis for 4 dB site acceptability criterion (see Clause 5)	99
Bibliography	101
Figure 1	– Schematic of radiation from EUT reaching an LPDA antenna directly and via ground reflections on a 3 m site, showing the half beamwidth, φ , at the reflected ray.....	15
Figure 2	– Obstruction-free area of a test site with a turntable (see 5.2.3).....	21
Figure 3	– Obstruction-free area with stationary EUT (see 5.2.3)	21
Figure 4	– Configuration of equipment for measuring site attenuation in horizontal polarization (see 5.2.6 and Annex E)	23
Figure 5	– Configuration of equipment for measuring site attenuation in vertical polarization using tuned dipoles (see 5.2.6 and Annex E).....	24

Figure 6 – Typical antenna positions for alternative test site – Vertical polarization NSA measurements	28
Figure 7 – Typical antenna positions for alternative test site – Horizontal polarization NSA measurements	28
Figure 8 – Typical antenna positions for alternative test site – Vertical polarization NSA measurements for a smaller EUT	29
Figure 9 – Typical antenna positions for alternative test site – Horizontal polarization NSA measurements for a smaller EUT	29
Figure 10 – Graph of theoretical free-space NSA as a function of the frequency for different measurement distances (see Equation (10))	33
Figure 11 – Measurement positions for the site validation procedure.....	35
Figure 12 – Example of one measurement position and antenna tilt for the site validation procedure	36
Figure 13 – Typical free-space reference site attenuation measurement set-up.....	39
Figure 14 – Position of the antenna relative to the edge above a rectangle set-up table (top view).....	42
Figure 15 – Antenna position above the set-up table (side view)	42
Figure 16 – Example of a typical paddle stirrer	43
Figure 17 – Range of coupling attenuation as a function of frequency for a chamber using the stirrer shown in Figure 16	44
Figure 18 – Transmit antenna <i>E</i> -plane radiation pattern example (this example is for informative purposes only)	48
Figure 19 – Transmit antenna <i>H</i> -plane radiation pattern (this example is for informative purposes only)	49
Figure 20 – S_{VSWR} measurement positions in a horizontal plane (see 8.3.3.2.2 for description).....	50
Figure 21 – S_{VSWR} positions (height requirements).....	52
Figure 22 – Conditional test position requirements.....	58
Figure 23 – Definition of the reference planes inside the test jig.....	60
Figure 24 – The four configurations for the TRL calibration	62
Figure 25 – Limits for the magnitude of S_{11} , measured according to provisions of 9.1 to 9.3 ...	63
Figure 26 – Example of a 50 Ω adaptor construction in the vertical flange of the jig.....	64
Figure 27 – Example of a matching adaptor with balun or transformer.....	65
Figure 28 – Example of a matching adaptor with resistive matching network	65
Figure A.1 – Short dipole antenna factors for $R_L = 50 \Omega$	69
Figure B.1 – Method using network analyzer.....	75
Figure B.2 – Method using measuring receiver and signal generator	76
Figure B.3 – Example of capacitor mounting in dummy antenna.....	76
Figure C.1 – The loop-antenna system, consisting of three mutually perpendicular large-loop antennas	79
Figure C.2 – A large-loop antenna containing two opposite slits, positioned symmetrically with respect to the current probe C	80
Figure C.3 – Construction of the antenna slit	81
Figure C.4 – Example of antenna-slit construction using a strap of printed circuit board to obtain a rigid construction	81
Figure C.5 – Construction for the metal box containing the current probe.....	82
Figure C.6 – Example showing the routing of several cables from an EUT to ensure that there is no capacitive coupling from the leads to the loop.....	82